

INVITATION TO BID (ITB)

Vendor/Company Name : _____ Date : __/__/2025

Cell phone :

| | |
|--|---|
| Date: 18 th May, 2025 | No. of pages including this page: 10 |
| Tender title: ITB for Rehabilitation of Midnimo HF-Dhobley. | Ref no: A05_SO_WVSJL FY25-119 |

Closing deadline: 1st June 2025 at 04:00PM

Manner of Submission:

ALL quotations/bids must be submitted through somo_supplychain@wvi.org The subject of the Email should be 'ITB Rehabilitation of Midnimo HF-Dhobley'

Invitation to bid

World Vision Somalia Program SCZ Office invites qualified and reputable Contractors with proven experience in provision of Rehabilitation of Midnimo HF-Dhobley to make an offer based upon the conditions stated in this invitation to tender for the following Items in **Annex I**

Important:

Offers transmitted in any other manner than those indicated above will not be considered.

Evaluation Criteria

Your bid will be evaluated as indicated below

EVALUATION CRITERIA FOR BUILDING WORK PROJECTS

Stage 1: Preliminary Bid Responsiveness Assessment (Mandatory Requirements)

This will involve assessing whether bidders have complied with submission requirements and have also attached copies of mandatory eligibility and statutory documents. Evaluation at this stage will be conducted on **Yes/No**, and bidders are expected to **comply with ALL** required items so as to proceed to the next stage of evaluation.

| No. | Completeness and Responsiveness Criteria | Requirement |
|-----|--|--|
| 1. | Tax certificate | -Provide a certified copy of tax registration, tax clearance certificates or similar documents |
| 2. | Business registration | -Provide a certified copy of a certificate of business registration, certificate of incorporation, business license or similar document and stamped from Luuq or respective District Council or Authority. |

Stage 2: Technical Responsiveness Evaluation Stage

Tenders will be evaluated to ensure that they are substantially responsive to the technical specifications and contract conditions stated in the Tender Document. The determination of a tender's technical responsiveness will be based on the contents of the tender itself, subject to any clarifications received in the preliminary examination of Tenders. Items of this evaluation will be scored as below.

| Item | DESCRIPTION | | POINT Score (marks) |
|------|---|---|---------------------|
| I | EXPERIENCE | | Max 30 |
| | Attach practical completion certificate with respective contracts ONLY for past successfully delivered projects as evidence: | | |
| | I.1 Value of similar/related Water works handled in \$. | | |
| a. | Six similar/related projects of equal or higher value done in the last four years @5 Mks | 6 contracts of similar work of equal or higher value @ 3marks Six completion certificates of similar work of equal or higher value @2 marks | 30 |
| 2. | KEY PERSONNEL – (To be edited based on specialty of skills required) | | Max 25 |
| | Technical skill in terms of human resource. Attached CVs and certified copies of academic certificates detailing qualifications of key personnel who shall be involved in these assignments. The persons must be working with the organization or sign on undertaking to work with the firm by the time of submitting this tender throughout the job if awarded. Each of the personnel will be evaluated on the following parameters. | | |
| a. | Project Manager (At least a diploma in Civil/water, Structural Engineering OR Construction Management). | Technical Qualification – At least a diploma in Civil/Water or structural Eng. (4Mks). Experience in years 6 years total, 5 years in similar works (6 Mks) | 10 |
| b. | Site Supervisor/Foreman (Max 5Marks) (Diploma in civil/Water/structural engineering) | Technical Qualification – Diploma in civil/ water engineering (2Mks) Experience in years 3 years total, (3 Mks) | 5 |
| c. | Mason | Technical qualification _ Grade Test, (2 Mks) Experience in years (Min 2 years) (3Mks) | 5 |
| e. | Plumber | Technical qualification _ Certificate (2Mks) Experience in years (Min 2 years) (3Mks) | 5 |
| 3 | PLANT AND EQUIPMENT – (Edited as per requirement of the specific job – State the specific machinery required and how many) | | Max 15 |
| | Relevant Equipment | No. Equipment and Plant owned by the Company, Evidence of ownership or lease agreement for any related equipment 3 Marks for each relevant equipment for the proposed works 1. Concrete vibrator poker type N.D. 40-90 mm (1No.), 2. Tipper Truck 10 ton (1No.) or higher tonnage 3. Dewatering pump (1No.), 4. Plate compactor 5. Concrete mixer 6. Geotextile laying equipment (3 Mks for each equipment) | 15 |

| Item | DESCRIPTION | POINT Score (marks) |
|------|--|---------------------|
| 4. | WORK METHODOLOGY | Max 10 |
| | Program of works logically applicable to this task. Detail the exact time expected to complete the assignment. | 10 |
| | Detail Methodology _ Logically articulated and including issues of safety, environment and social safeguards | 20 |
| | TOTAL | MAX 100 |
| | REMARKS | |

NB:

1. Pass mark for technical evaluation will be **70%**
2. The contractors who attain the pass mark at technical evaluation will then be taken through the financial evaluation
3. World Vision Somalia will award the Contract to the tenderer whose tender is determined to be substantially responsive to the tender documents and who has offered the technically acceptable evaluated tender price.

Your offer should and MUST clearly indicate:

1. Unit price;
2. Confirmed delivery schedule;

Information to bidders:

1. Currency of offer should preferably be in US Dollars, but in case local currency is offered, the comparison of offers will be based on the prevailing rate of exchange.
2. World Vision does not undertake to pay by letter of credit (LOC) or in advance of work completion.
3. World Vision reserves the right to accept the whole or part of your offer.
4. World vision Somalia reserves the right to accept or reject any application (bid), and is not bound to give reasons for its decisions. Canvassing or giving false information will lead to automatic disqualification.
5. Your quotation letter can be separate page/s from world vision international Somalia ITB/RFQ.
6. ALL quotations/bids must be submitted through somo_supplychain@wvi.org on/before the deadline on **1st June 2025 at 04:00PM** and the subject of the Email should be '**ITB_ Rehabilitation of Midnimo HF-Dhobley**'.
7. The supplier/Contractor must obtain Registration/ clearance letter, signed and stamped from respective District Council or Authority.

I. Cost

Cost evaluation will be based on the cost quoted for the attached BOQ in Annex I.

All pages and corrections should be counter signed (if any);

Please acknowledge this tender and indicate your interest to bid.

Best Regards,
Supply chain, Jubaland,
World vision-Somalia.

Annex I: BOQ Rehabilitation of Midnimo HF-Dhobley:

| | Rehabilitation of Midnimo HF-Dhobley | | | | |
|-------------|--|-------------|-----------------|-----------------------|-------------------------|
| ITEM | DESCRIPTION | UNIT | QUANTITY | RATE (USD) | AMOUNT (USD) |
| 1 | Clean all rooms and toilets by removing debris, dust, and leftover materials. | Ls | 1 | | |
| 2 | Painting: Prepare and apply two coats plastic emulsion paint to external and internal walls (Sadolin WeatherGuard, or Crown Permacote Ultra paint). Paint will be applied for all the HF rooms corridors and external walls | m2 | 960 | | |
| 3 | Metal Windows: Replacement of damaged wooden windows with new metal windows with metal grills of current window size applied two coats of anti rust paint and two coat of emulsion paint as will be directed by the supervising engineer | No | 10 | | |
| 4 | Metal doors: Replacement of damaged Doors windows with new metal Doors of current Door size applied two coats of anti rust paint and two coat of emulsion paint as will be directed by the supervising engineer | No | 2 | | |
| 5 | Door Locks and Hinges: Replacement with fixing hinges and locks, with all necessary accessories for installed existing doors | No. | 5 | | |
| 6 | Pharmacy Shelves: supply and installation of 18mm moisture and termite-resistant plywood shelves with a laminated or polished finish. The shelves will be wall-mounted using stainless steel brackets and secured with appropriate fasteners. | M2 | 45.5 | | |
| 7 | Supply and install wash Basin for the maternity room, The grey water from the sink will be connected to the existing septic tank, the rate will include all piping, fittings, manholes, all labor, materials, accessories, tools and equipment necessary to complete the Work. | Pcs | 2 | | |

| | | | | | |
|-----|---|-----|-----|--|--|
| 8 | Combined ramp and step entrance and landing: a ramp with a maximum slope of 1:12, at least 1m wide, with non-slip surfaces, handrails on both sides and landings. Steps have risers no higher than 150mm, treads at least 250mm deep, non-slip surfaces, as shown in the design and as directed by WV Engineer | Ls | 1 | | |
| 9 | Storage water tank and water connection | | | | |
| 9.1 | Supply and fix 5000 ltr heavy duty HDPE water tank including All necessary plumbing fittings and connect to the toilets as directed by the engineer | Pcs | 1 | | |
| 9.2 | Tank Base: Construct 1.5mx1.5mx1.2m tank base of masonry block wall filled with hardcore under the tank, 25mm plaster and applied with two coats of emulsion paint as will be directed by the supervising Engineer | Ls | 1 | | |
| 9.3 | Tank Shade: Install 4 pcs of GI pipes with 3.5m height and Shade the plastic water tank with G28 sheets including timber truss and all other accessories | Ls | 1 | | |
| 9.4 | Supply and install Heavy duty PPR pipe 1.5-inch diameter including all its connectors with its joints and sockets from HDPE water tank and distributes to the maternity ward, Toilet | Lm | 100 | | |
| 11 | Toilet near maternity room: Handwashing Basin, Taps, Shower Head and Toilet Seat: Supply and Install 1 Handwashing Basin of size 300mm x 450mm, two taps, one shower head and 1 Complete WC with flushing and all fixing supports installed in the Maternity WC | | 5 | | |
| 12 | Plumbing works: contractor is required to Test the existing sewer lines, manholes, WC, Wash Basin, Shower and Water taps and do all fitting repairs/replacement of pipes required. | Ls | 1 | | |

| | | | | | |
|-------------|--|-------------|-----------------|-------------------|---------------------|
| 13 | Branding: using Sadolin WeatherGuard, or Crown Permacote Ultra Paint.-Provide well painted Logo for World vision, ECHO-(The Donor Logo) and MOH combined and printed both Somali and English on the wall of the rehabilitated Health Facility- Message wording- (Xaruntan caafimaad waxa dib-habeyn ku samaysay World Vision waxaana maalgalisay DG-ECHO) and English- (This Health Facility was rehabilitated by World Vision Somali with funding support from DG-ECHO). Remember This will be directed by the supervising engineer. | Job | 1 | | |
| | TOTAL COST | | | | |
| | Midnimo waiting area BOQ | | | | |
| ITEM | DESCRIPTION | UNIT | QUANTITY | RATE (USD) | AMOUNT (USD) |
| A | SUBSTRUCTURE | | | | |
| 1 | Site Clearance: Clear obstacle trees, vegetation, small trees, scrubs, and bushes and Prepare site by stripping top 200 mm of soil to remove all debris | m2 | 1075 | | |
| 2 | Excavation for waiting area: Excavate for Stone Foundation and Remove surplus excavated material from site | m3 | 10.08 | | |
| 3 | Stone Foundation for waiting area: 300mm Thick rubble stone foundation walling in cement and sand mortar (1:3) | m2 | 12 | | |
| 4 | Waiting Area Hard Core: 300 mm thick approved hardcore filling spread, well rammed and compacted in 150mm layers to receive a concrete surface bed | m3 | 10.5 | | |
| 5 | Plinth beam for waiting area: Construct a Reinforced Concrete class 25, 200mm Plinth beam over the stone foundation. Use 4D12 reinforcement bars | m3 | 1.92 | | |
| 6 | Waiting Area Floor slab: 100mm thick floor slab with surface steel trowelled smooth. Use A142 BRC mesh for reinforcement | m3 | 3.5 | | |
| | SUB TOTAL FOR SUBSTRUCTURE | | | | |

| B | SUPERSTRUCTURES | | | | |
|----|---|----|------|--|--|
| 1 | Waiting area Walling: 200mm Thick, 1500 mm high Hollow block walling for the waiting area | m2 | 27 | | |
| 2 | Concrete Block Seating Benches for waiting area: 500mm Thick, 500 mm high, and 2m long Concrete block seating benches for the waiting area as directed by the Engineer | No | 10 | | |
| 3 | Waiting area Columns: Construct a Reinforced Concrete class 25, 300mm by 300mm Column for the waiting area. Use 4D12 reinforcement bars | m3 | 2.43 | | |
| 4 | Waiting area Top tie Beam: Construct a Reinforced Concrete class 25, 200mm Top tie beam over the stone foundation. Use 4D12 reinforcement bars | m3 | 2.16 | | |
| 5 | Waiting Area Roofing: supply and Install 28 Gauge galvanized corrugated iron sheets fixed to sawn celcured cypress timber truss constructed of 100mm x 50mm Rafters, 100mm x 50mm wall plate, and 50mm Purlins. | m2 | 35 | | |
| 6 | Waiting Area Ceiling: Supply and install 9mm thick Marine Plywood (BWP Grade) | m2 | 35 | | |
| 7 | Fascia Board: Supply and Install 200mm x 25mm celcured cypress timber Fascia Board. This includes the waiting area and the main facility | m | 67.8 | | |
| 8 | Combined ramp and step entrance and landing: a ramp with a maximum slope of 1:12, at least 1m wide, with non-slip surfaces, handrails on both sides and landings. Steps have risers no higher than 150mm, treads at least 250mm deep, non-slip surfaces, as shown in the design and as directed by WV Engineer | Ls | 2 | | |
| 9 | Waiting Area Floor finish: Finish the floor with 30mm thick steel trowelled screed. Use Cement and sand mortar (1:3) | m2 | 35 | | |
| 10 | Waiting area Tiles: Supply and Install Non-slip approved ceramic floor tiles size 300mm x 300mm x 8mm thick as approved by the Engineer, bedded on cement and sand screeds in floors, including 1000mm high skirting to a junction with floor and wall finish. | m2 | 35 | | |

| | | | | | |
|----|---|-----|----|--|--|
| 11 | Plaster: Plaster 12 mm Thick mortar rendering with steel float finish to masonry and concrete surfaces. Use Cement and sand mortar (1:3) | m2 | 81 | | |
| 12 | Painting: Prepare and apply three coats of Sadolin WeatherGuard, or Crown Permacote Ultra Paint paint to Plastering surfaces | m2 | 81 | | |
| 13 | Branding Services: Branding: using Sadolin WeatherGuard, or Crown Permacote Ultra Paint.-Provide well painted Logo for World vision, ECHO-(The Donor Logo) and MOH combined and printed both Somali and English on the wall of the rehabilitated Health Facility-Messagae wording-(Xaruntan caafimaad waxa dib-habeyn ku samaysay World Vision waxaana maalgalisay DG-ECHO) and English-(This Health Facility was rehabilitated by World Vision Somali with funding support from DG-ECHO). Remember This will be directed by the supervising engineer. | Job | 1 | | |
| | SUB TOTAL FOR SUPERSTRUCTURE | | | | |
| | TOTAL COST | | | | |

| | Midnimo MCH Fencing BoQ | | | | |
|------|---|------|----------|------------|--------------|
| ITEM | DESCRIPTION | UNIT | QUANTITY | RATE (USD) | AMOUNT (USD) |
| 1 | Excavation: Excavate holes size 200mm diameter by 1000mm deep to receive posts. Spacing to be 2000mm. (holes for the upright posts, the strainer posts, and the bracing posts) | m3 | 21.98 | | |
| 2 | Angle Posts: Supply and install 75mm x 75mm x 6mm thick cranked angle posts at 2000mm centers morticed in mass concrete surround. The posts are to be 2.5m in length | No | 35 | | |
| 3 | Strainer and Bracing poles: Supply and install as above but for strainer and bracing poles spaced at 5m intervals | No | 14 | | |
| 4 | Barbed Wire: Supply and install 5 Strands of gauge 14 double-strand-standard galvanised barbed wire | m | 350 | | |

| | | | | | |
|----------------------------------|--|------|-----|--|--|
| 5 | Chainlink: Supply and install 2000mm High-quality chainlink (Gauge 10), morticed in mass concrete surround | Roll | 4 | | |
| 6 | Mass Concrete: Cast a mass concrete (1:3:6) base of 0.2m x 0.3m to firm the Bottom of the fencing to the ground | m3 | 4.2 | | |
| 7 | Columns: Construct 5 Reinforced Concrete class 25, 300mm by 300mm Columns at the Gate sides as a door support and anchorage. Use 4D12 and D8@200mm for reinforcement bars | m3 | 0.6 | | |
| 8 | Entrance Gate: 2,000mm high x 3,000mm wide mild steel gate including all the necessary ironmongery | No | 1 | | |
| 9 | Doors: 2,000mm high x 3,000mm wide mild steel gate including all the necessary ironmongery. | No | 1 | | |
| 10 | Branding Services: Prepare a a big metallic branding plate and Billboards with world vision and partner Logo with wording and other project information to be welded to the gates as directed by the engineer | Job | 1 | | |
| TOTAL COST OF CFS FENCING | | | | | |

| | Solar System BoQ | | | | |
|------|---|------|----------|------------|--------------|
| ITEM | DESCRIPTION | UNIT | QUANTITY | RATE (USD) | AMOUNT (USD) |
| 1 | Supply and Installation Solar panels of Monocrystalline or equivalent (Pmax= 550W, Voc= 49.9V, Vmp= 41.96V, Isc= 14A, Imp= 13.11A at standard test conditions). Provide data sheets for any alternative offered. Note that the Solar panels will be installed on the roof | Pcs | 8 | | |
| 2 | Solar Inverter (for 6.2kW capacity) | Pcs | 1 | | |
| 3 | Lithium/lead-acid solar battery (12V, 200Ah each) | Pcs | 4 | | |
| 4 | Ceiling Fans, Lighting bulbs, wiring, switches: Supply and Install 6 Ceiling fans (40W) and 10 lighting bulbs (10W), switches for each room, 2 sockets for each room and 10 AWG wires for wiring the whole system | Unit | 1 | | |

| | | | | | |
|---|---|-----|---|--|--|
| 5 | Any other solar accessories and solar packages including wiring assessories for the solar panels and any other that may have not been explicitly covered in this BOQ. Including U/G Cables,Earthing etc | LSM | 1 | | |
| 6 | Mounting Structure on the roof with high-grade extruded aluminum or galvanized steel for strength, corrosion resistance, and lightweight properties with all required fastenered | LSM | 1 | | |
| 7 | Transportation, installation, testing and commissioning the solar system | LSM | 1 | | |
| | Grand Total | | | | |
| | | | | | |
| | Grand Total for Midnimo HF-Rehabilitation+Sub Total for Midnimo waiting area+Sub Total For Midnimo MCH Fencing+Sub Total Solar System procurement and Installation | | | | |

| Summary Sheet for Midnimo HF-Dhobley | | |
|--------------------------------------|---|--------|
| S.No. | Description | Amount |
| 1 | Minor rehabilitation works of the HF building | |
| 2 | Waiting area with shade | |
| 3 | Perimeter chainlink Fencing | |
| 4 | Solar system | |
| | Total | |